OHNERAL NOTES

Nebraskal at the time Nebraskal at the time priselismic Site Class D. dinay vary from lance with an income.

Hoor: 40 per, live 15 per, dead Soll bearing Capacity - 1500 psf.

Roof: 30 psf, live 10 psf, dead

Celling: IO per, IIve

Live loads, dead loads, sind loads, some loads, stemil loads, settemil or on the confidence of the control of t

CRETTE AND POLYDATIONE:
Il foundation wills and sizes on grade shall be 3000 Pbil
Il foundation wills and sizes on grade shall be 3000 Pbil
Il martin sizes on grade shall bear on 4" comparated granular
Ill martin sizes on grades shall bear on 4" comparated granular
Ill with 6 mil polystrijares vapor barines underseath,
and the polystrijares vapor barines underseat tion walls are not to be backfilled until properly eants. 36" x 18" concrete pads to have (3) #5 rods 48" x 24" concrete pade to have (4) *5 rode

frost footings with your local codes, protection as required by HUD minimum de.

"If the country is teal for bears and plotes shall comply up half to execute on a "Seal country and all societized free literations and comply units ASTM specialization ASS depailed for ASSM comply units ASTM shall be concluded as the shall for concluded while comply units ASTM for other states of the concluded as the shall be all possible country are to be 3" I.D. (fielde diameter) unless concern otherwise.

IntiA integrate, in fraing lution wall have the ligation of control of the first the property of the pipuling control of the first the property of property

ill mellock, sold or floor plans are at 45 degree angle, ill mellock production of the production of triend, indisa rotated childrains above all openings that as indisa rotated childrains above all openings that as indisa rotated childrains above all openings that it is considered and the sold of the constant of

All examples offeres whell be provided in each ofference with learning large given by the provided in the provided in each ofference with learning large given by the provided g

MIGO. NOTES:

Preferridad freplaces and flues are to be U.L. approved and insulied as per manifeturer's specifications.

All materials, upplies and appriment to be insulied as per manifeturer's specifications and per local codes and accommensure.

recultivements.

recult

McCaffery

Rainbow Restoration Of Rockwood

advancedhouseplans



McCaffery

Rockwood Ontario N0B 2K0 118 Alma st

advanced houseplans

ictural or framing members not indicated on the plan be sized by contractor. Floor Joists under all partition walls, unless noted for s. poring is assumed to be 3/4" thick, glued 4 relied. for walls are dimensioned to outside of 1/2" sheathing addimensions take precedence over scaled re.













